

HT- M Series

Dual Channel

The HTDZ HT-M series amplifiers offer a package of reliable high-output power, high efficiency, and legendary pro audio performance. They are the premium choice as system drives for a variety of applications like auditoriums, houses of worship, outdoor portable applications, and conferences. Ranging from 600 to 4500 watt HT-M Series is a flexible choice for driving any kind of PRO Speakers series.



Specifications

Model number	HT-M200	HT-M300	HT-M450	HT-M600	HT-M800	HT-M1000	HT-M1200	HT-M1500
Consumption 8Ω	2x200W	2x300W	2x450W	2x600W	2x800W	2x1000W	2x1200W	2x1500W
Consumption 4Ω	2x300W	2x450W	2x675W	2x900W	2x1200W	2x1500W	2x1800W	2x2250W
Consumption 8Ω Bridged	600W	900W	1350W	1800W	2400W	3000W	3600W	4500
Frequency Response	20Hz-20kHz							
T.H.D (8Ω/ 1Khz)	<0.5% (20Hz-20kHz)							
Switching Rate	10V/ μ s							
Damping Coefficient	>200dB							
Input sensitivity	0.77V, 1.4V, 32dB							
Input Impedance	UNBAL 10KΩ / BAL20KΩ							
Voltage Gain	33dB/36dB/39dB/41dB							
Connectors	Input:XLR(Mx2 + FX2) Output SpeakONx2; PK-BFAX4							
S/N Ratio	≥ 100dB							
Protection and cooling	Returned switch(ss);DC fault disconnect;active inrush limiting;Short/open circuit:Overload/ overheating protection							
Dimention (mm)	483 x 88.9 x 482							
Net Weight	10kg	10.5kg	11kg	12kg	14kg	16kg	18kg	20kg